

PRODUCT DESCRIPTION

Form Seal is a hard, pre catalyzed polyurethane coating having outstanding abrasion, wear, and chemical resistance. The film has a high degree of flexibility and works well to pre-treat wood and concrete form work where medium re-use of up to 40 casts are expected.

USES

Effectively seals concrete forming materials for multiple uses

FEATURES

- Chemical resistant
- Heat resistant up to 200°F
- Abrasion resistant
- High re-use rate for forms

COVERAGE RATES AND PACKAGING

- Coverage rates will vary between 150-200 square feet/gallon depending on the porosity of the substrate to be coated.
- Packaged in 5 Gallon steel pails

STORAGE & SHELF LIFE

Store in a dry area

Shelf life is three years from date of manufacture.

USE & APPLICATION

Be sure the forms are clean, dry, and free of any grease or oils prior to use. Brush, roll, or spray the Form Seal on to the form. Apply additional coats (up to 3) are applied to a tacky surface to assure proper bonding between layers. If the Form Seal completely dries between coats, lightly sand the surface with 80 grit sandpaper to create a profile for better adhesion between layers.

Once dry, the forms can now be treated with the Altus/Altus VOC products.

Once used, the forms can be cleaned with Citri-Solv and will be ready for the next application of the Altus products.

MAINTENANCE

Keep forms clean with Citri-Solv

Once the Form Seal starts to show wear, after cleaning with Citri-Solv, sand the surface with 80 grit sandpaper and thoroughly clean the surface. Once clean and dry, re-apply 1-2 coats of Form Seal.

RECOMMENDED TOOLS & CLEAN UP

- Solvent resistant brushes and roller covers
- 80 Grit Sandpaper

COMPLEMENTARY PRODUCTS

- Citri-Solv
- Brickform E-Etch
- Brickfor Neutra Clean
- Altus/Altus VOC

SAFETY & PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Do not breathe vapors or mist. Use only with adequate ventilation and use a respirator when levels are above applicable limits. Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

For more information go to:

SolomonColors.com or brickform.com

