PANEL FINISH

PRODUCT DESCRIPTION

Architectural Concrete Chemicals Panel Finish is a special cleaner for architectural precast in particular and all concrete in general where general purpose cleaning is necessary and surface etching is of concern. It combines a blend of mild, fumeless acids and inhibitors, which clean and brighten exposed aggregate concrete, in particular without frosting or burning the aggregates as when using muriatic acid or hydrochloric based cleaners.

USES

Used for cleaning architectural and structural panels after long periods of storage at the plant or at the site. Safe for use even after the installation of windows and doors, when accompanied with proper pre-wetting of the surfaces prior to use.

FEATURES

- Non-hydrochloric acid based concrete cleaner
- No frosting of the surface
- Odorless formula

COVERAGE RATES AND PACKAGING

- 200-250 ft/gal
- 5 gal. plastic pails. 55 gal. plastic drums

STORAGE & SHELF LIFE

Two years from manufacturing date in closed original container.

USE & APPLICATION

Use concentrated or dilute with up to 4 parts water. Apply to the pre-wet surface with a brush and scrub vigorously. Flush sufficiently with water. Re-apply if necessary.

SAFETY & PRECAUTIONS

CORROSIVE. KEEP OUT OF REACH OF CHILDREN. Before using or handling this product, read the Safety Data Sheet (SDS), product label, and warranty information. Do not take internally. Avoid breathing vapors, spray, or mist. Use only with adequate ventilation. When ventilation is insufficient or exposure limits may be exceeded, use appropriate respiratory protection. Avoid contact with eyes, skin, and clothing. Corrosive to eyes and skin. Wear appropriate protective gloves, protective clothing, and eye/face protection. Wash thoroughly after handling. Remove and wash contaminated clothing before reuse. Keep container tightly closed when not in use. Store in a cool, dry location in a corrosion-resistant container with a resistant inner liner. Protect from freezing. Do not mix with incompatible materials. FIRST AID: In case of eye contact, immediately flush with water for at least 15 minutes while holding eyelids open. Remove contact lenses if present and easy to do. Seek immediate medical attention. In case of skin contact, immediately remove contaminated clothing and flush skin with plenty of water for at least 15 minutes. Seek medical attention if irritation or burns occur. If inhaled, move the person to fresh air and seek medical attention if symptoms persist. If swallowed, rinse mouth. Do not induce vomiting. Immediately contact a Poison Control Center or physician and seek emergency medical attention.

WARRANTY

Solomon Colors / ACC Products are intended for use by licensed contractors and installers, experienced and trained in the use of these types of products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing ACC products proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

PANLFIN-5

PANLFIN-55

For more information go to:
Solomoncolors.com/ACC

INFORMATION



© 2022 Solomon Colors, Inc., All rights reserved.