RELEASE 80

PRODUCT DESCRIPTION

Architectural Concrete Chemicals Release 80 is an all-weather, non-staining release agent for easy void free and smooth release of concrete. Release 80 yields very high-quality architectural concrete finishes. The release provides corrosion inhibition of steel forms, very high heat resistance with no powdery residues.

USES

Apply Release 80 by brush, roller, sprayer, lightly oiled mop or by fogger on steel, sealed concrete, coated wood and fiberglass molds, Plexiglas and other synthetic mold surfaces. For the ultimate in positively void-free snow-white smooth castings. Release 80 yields a high-performance, hard surface finish and can be used on white or gray cements surfaces with equal results.

FEATURES

- All weather
- Non staining
- Use with white or gray cements
- No powdery residue

COVERAGE RATES AND PACKAGING

- 3,000 -5000 sq.ft. / gal.
- 5-gal plastic pails, 55-gal plastic drums.

STORAGE & SHELF LIFE

Two years from manufacturing date in closed original container.

USE & APPLICATION

Remove any oil or grease residues from the form surface left from previously used releases. Apply Release 80 onto the forms at a rate of 3,000 -5000 sq.ft. / gal. Wipe out excess oil with a slightly oil moistened mop or rag. Allow release to dry prior to concrete placement.

SAFETY & PRECAUTIONS

FLAMMABLE LIQUID. KEEP OUT OF REACH OF CHILDREN Before using or handling this product, read the Safety Data Sheet (SDS), product label, and warranty information. Do not take internally. Avoid breathing vapors, spray, or mist. Use only with adequate ventilation. When ventilation is insufficient or exposure limits may be exceeded, use appropriate respiratory protection. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before reuse. Keep container tightly closed when not in use. Do not use near heat, sparks, open flames, or other sources of ignition. Store in a cool, dry location. Protect from freezing. FIRST AID: In case of eye contact, flush thoroughly with water for at least 15 minutes. If irritation persists, seek medical attention. Wash skin thoroughly with soap and water after contact. If swallowed, do not induce vomiting. Seek immediate medical attention or contact a Poison Control Center.

WARRANTY

Solomon Colors / ACC Products are intended for use by licensed contractors and installers, experienced and trained in the use of these types of products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing ACC products proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

REL80-5

REL80-55

For more information go to:
Solomoncolors.com/ACC

INFORMATION



© 2022 Solomon Colors, Inc., All rights reserved.