TUFF RELEASE

PRODUCT DESCRIPTION

Architectural Concrete Chemicals Tuff Rlease is a semi-Liquid, high viscosity release which ensures the highest quality architectural and structural surfaces. Will not stain the concrete or affect adhesion of waterproofing or other coatings.

USES

Designed for use with the most intricate molds and forms, especially with low or no draft applications and when using highly superplasticizer (SCC) mixes. May be used on all types of formwork including plastic, rubber or styrofoam.

FEATURES

- High viscosity
- Use with SCC mixes
- Use on all types of form work
- Non staining

COVERAGE RATES AND PACKAGING

- 5-gal plastic pails, 55-gal plastic drums

STORAGE & SHELF LIFE

Two years from manufacturing date in closed original container.

USE & APPLICATION

Remove any oil or grease residues from the form surface left from previously used releases. Apply Tuff Release in a very thin coat by brush, roller or by spray using a high-volume low-pressure spray gun or by jiffy mop with on a swivel assembly. Wipe out excess oil with a slightly oil moistened mop or rag. Allow surface to dry prior to concrete placement.

SAFETY & PRECAUTIONS

CAUTION: KEEP OUT OF REACH OF CHILDREN Before using or handling this product, read the Safety Data Sheet (SDS), product label, and warranty information. Do not take internally. Avoid breathing vapors, spray, or mist. Use only with adequate ventilation. When ventilation is insufficient or exposure limits may be exceeded, use appropriate respiratory protection. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before reuse. Keep container tightly closed when not in use. Do not use near heat, sparks, open flames, or other sources of ignition. Store in a cool, dry location. Protect from freezing. FIRST AID: In case of eye contact, flush thoroughly with water for at least 15 minutes. If irritation persists, seek medical attention. Wash skin thoroughly with soap and water after contact. If swallowed, do not induce vomiting. Seek immediate medical attention or contact a Poison Control Center.

WARRANTY

Solomon Colors / ACC Products are intended for use by licensed contractors and installers, experienced and trained in the use of these types of products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing ACC products proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

VOC content is < 350 g/L

TR-5

TR-55

For more information go to:
Solomoncolors.com/ACC

INFORMATION



© 2022 Solomon Colors, Inc., All rights reserved.