



# SAFETY DATA SHEET

Issue Date 17-Aug-2020

Revision Date 17-Aug-2020

Version 1

BPG

Brickform Gem-Guard SB 600

## 1. IDENTIFICATION

### Product identifier

**Product Name** Brickform Gem-Guard SB 600

### Other means of identification

**Product Code** BPG

### Recommended use of the chemical and restrictions on use

**Recommended Use** Restricted to professional users.

**Uses advised against** Consumer use

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Solomon Colors, Inc.  
4050 Color Plant Road  
Springfield, IL  
62702

**Company Phone Number** 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

**24 Hour Emergency Phone Number** 800-373-7542

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This product is classified as hazardous according to the criteria contained in the Hazard Communication Standard 29 CFR 1910.1200 (known as HCS 2012).

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3 (respiratory, central nervous system)
Specific target organ toxicity (repeated exposure)	Category 2 (liver, kidneys, central nervous system)
Flammable liquids	Category 2

### Label elements

#### **Emergency Overview**

**Danger**

#### **Hazard statements**

Harmful if inhaled

Causes skin irritation  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause respiratory irritation  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor



**Appearance** Clear to slightly hazy liquid

**Physical state** Liquid

**Odor** Aromatic

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
Specific treatment see section 4 of the SDS.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
If skin irritation occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
IF SWALLOWED: Immediately call a POISON CENTER or doctor  
Do NOT induce vomiting  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

#### **Hazards not otherwise classified (HNOC)**

#### **Other Information**

• Toxic to aquatic life

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%	Trade Secret
Tet-Butyl Acetate	540-88-5	20-30	*
Petroleum naphtha, light aromatic	64742-95-6	15-30	*
Acetone	67-64-1	20-30	*
Acrylic Polymer	Proprietary	10-20	*
Trimethylbenzene, Isomers	25551-13-7	14-17	*
1,2,4 Trimethylbenzene	95-63-6	5-12	*
Cumene	98-82-8	1-2.8	*
Xylenes (o-, m-, p- isomers)	1330-20-7	0-1.4	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret. This product contains nonhazardous, proprietary alkylsilane and alkylsiloxane. This product also contains trace amounts of benzene (impurity).

## 4. FIRST AID MEASURES

### Description of first aid measures

<b>General advice</b>	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin Contact</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult.
<b>Ingestion</b>	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May damage fertility and the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
-----------------	--

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Dry chemical, Carbon Dioxide, Foam, Sand. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

### Specific hazards arising from the chemical

**HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Keep product and empty container away from heat and sources of ignition. Do not allow run-off from fire-fighting to enter drains or water courses.

**Hazardous combustion products** Thermal decomposition can lead to the release of irritating gases and vapors. Carbon

oxides.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Keep people away from and upwind of spill/leak. Use personal protection recommended in Section 8. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded.

**Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

**Methods for cleaning up** Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal. Ground and bond containers when transferring material. Dike to collect large liquid spills.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Never pierce, drill, grind, cut, saw or weld any empty container.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not store near combustible materials. Use spark-proof tools and explosion-proof equipment.

**Incompatible materials** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

<b>Chemical Name</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>
Tet-Butyl Acetate 540-88-5	STEL: 150 ppm TWA: 50 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m <sup>3</sup>	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Trimethylbenzene, Isomers 25551-13-7	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m <sup>3</sup>	-
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-

NIOSH IDLH *Immediately Dangerous to Life or Health*

#### **Other Information**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### **Appropriate engineering controls**

##### **Engineering Controls**

Showers  
Eyewash stations  
Ventilation systems. Apply technical measures to comply with occupational exposure limits. However, it is the duty of the user to verify this and follow given exposure limits at the workplace.

#### **Individual protection measures, such as personal protective equipment**

##### **Eye/face protection**

Tight sealing safety goggles. Avoid contact with eyes.

##### **Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

##### **Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

##### **General Hygiene Considerations**

Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Aromatic
<b>Appearance</b>	Clear to slightly hazy liquid	<b>Odor threshold</b>	306 ppm
<b>Color</b>	Colorless		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No information available	
<b>Melting point/freezing point</b>	< -70 °C / -94 °F	
<b>Boiling point / boiling range</b>	56.1 °C / 133 °F	
<b>Flash point</b>	-17.8 °C / 0 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	12.8	
<b>Lower flammability limit:</b>	0.9	
<b>Vapor pressure</b>	26 kPa @20°C	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	No information available	
<b>Water solubility</b>	22.1% w/w	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	18-22 cP	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

### Other Information

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	< 600 g/L
<b>Density</b>	0.87 g/cc
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Prevent vapor accumulation.

### Incompatible materials

Strong oxidizing agents.

### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No acute toxicity information is available for this product The product is classified based on the mixture components.
<b>Inhalation</b>	Avoid breathing vapors or mists. May be harmful if inhaled. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Avoid contact with eyes. Contact with eyes may cause irritation.
<b>Skin Contact</b>	Prolonged contact may cause redness and irritation. Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance.
<b>Ingestion</b>	May be harmful if swallowed. Potential for aspiration if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tet-Butyl Acetate 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit ) > 2000 mg/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h > 9482 mg/m <sup>3</sup> ( Rat ) 4 h
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Acrylic Polymer	= 2500 mg/kg ( Rat )	-	= 1.71 mg/L ( Rat ) 4 h
Trimethylbenzene, Isomers 25551-13-7	= 8970 mg/kg ( Rat )	-	-
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h

### Information on toxicological effects

<b>Symptoms</b>	Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May damage fertility and the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
-----------------	--

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Skin Irritation Cat 2. (based on mixture components). Irritating to skin.
<b>Serious eye damage/eye irritation</b>	Eye Irritation Cat 2. Causes serious eye irritation. (Classification based on mixture components).
<b>Sensitization</b>	Not Classified. This product does not contain known sensitizers at levels > or equal to 0.1%.
<b>Germ cell mutagenicity</b>	Contains a known or suspected mutagen.
<b>Carcinogenicity</b>	Category 2: Substances that cause cancer in animals, and are considered to cause cancer in man. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Acrylic Polymer	-	Group 3	-	-
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - *Animal Carcinogen*

IARC (International Agency for Research on Cancer)

*Group 2B - Possibly Carcinogenic to Humans*

*Group 3 - Not Classifiable as to Carcinogenicity in Humans*

NTP (National Toxicology Program)  
*Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**Reproductive toxicity** Category 1B. Product is or contains a chemical which is a known or suspected reproductive hazard.

**STOT - single exposure** STOT SE 3 - Respiratory System. May cause irritation of respiratory tract. May cause dizziness or drowsiness.

**STOT - repeated exposure** Category 2. (Liver, Kidney, Central Nervous System).

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 6061 mg/kg  
**ATEmix (dermal)** 4950 mg/kg  
**ATEmix (inhalation-dust/mist)** 12.01 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Tet-Butyl Acetate 540-88-5	1.38
Acetone 67-64-1	-0.24
1,2,4 Trimethylbenzene 95-63-6	3.63
Cumene 98-82-8	3.7
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15

**Other adverse effects** No information available



### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Cumene 98-82-8	Toxic Ignitable
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable

## 14. TRANSPORT INFORMATION

### DOT

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Emergency Response Guide Number	128

### TDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

### MEX

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

### ICAO (air)

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

### IATA

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

### IMDG

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

### RID

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

### ADR

UN/ID no.	UN 1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0
Cumene - 98-82-8	1.0
Xylenes (o-, m-, p- isomers) - 1330-20-7	1.0

#### **SARA 311/312 Hazard Categories**

See section 2 for more information

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Tet-Butyl Acetate 540-88-5	-	-	-	X
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	-	X

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tet-Butyl Acetate 540-88-5	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

### US State Regulations

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65

Cumene - 98-82-8	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Tet-Butyl Acetate 540-88-5	X	X	X
Acetone 67-64-1	X	X	X
Trimethylbenzene, Isomers 25551-13-7	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X
Cumene 98-82-8	X	X	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<u>NFPA</u>	Health hazards 3	Flammability 3	Reactivity 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 3	Flammability 3	Physical hazards 0	Personal protection X

Prepared By Solomon Colors - Lab Technical Services  
Issue Date 17-Aug-2020  
Revision Date 17-Aug-2020  
Revision Note  
Initial SDS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**