

ColorSelect® Granular-to-Slurry System (GTS-RD)

with **NEW Rapid Discharge Feature**

The ColorSelect® GTS-RD System quickly meters ColorFlo® Granular pigment and mixes it with water for easy conveyance directly into the Ready Mix truck with no dust.



SYSTEM

- NEW! Rapid Discharge Feature
- Single, front loading access point
- Easy reloading
- Compact design allows for international shipping
- Windows-based PC control system and software
- Designed for Ready Mix producers using bulk super sack ColorFlo®
- Granular pigment
- Compact, modular, weatherproof design for quick installation
- Fast, accurate up to 11 cubic yard batches
- Pre-batch color so it is ready to go
- Dispenses directly into truck during batching process
- Built-in remote access for real-time technical support and software updates
- Capable of seamless integration to popular Ready Mix batching plant software
- Real-time video monitoring in weigh chamber



ColorSelect® Granular-to-Slurry System (GTS-RD)

with NEW Rapid Discharge Feature

EFFICIENT OPERATION

- Hopper holds up to 3,000 lbs of each pigment, allowing for continuous operation during color reload
- Internal water storage tank for consistent water pressure

INTELLIGENT ENGINEERING

- Weather-proof containers
- Climate controlled to prevent freezing
- Minimal use of water

ACCURACY & ACCOUNTABILITY

- Pigments metered individually for greater accuracy

FLEXIBILITY & ADAPTABILITY

- Built-in cellular connection for real-time technical support
- Discharge up to 100 feet from the dispenser



FOOTPRINT

- Base: 8' W x 10' L
- Clearance: 17' 6"
- Refill lift height: 10' 6"

REQUIREMENTS

- Electrical: 110 V, 30 Amp
- Dry, non-oil air: 100-120 PSI, min. 30 CFM
- Water: 40-50 PSI, 25 GPM. Water line must be protected from freezing

For a complete overview of the Color System along with Site Requirements, please contact your local Solomon Colors Representative.

